

# 2013 TITAN VS PRIMARY COMPETITORS



S = Standard  
A = Available  
N/A = Not Available

	2013 NISSAN TITAN	2013 CHEVROLET SILVERADO 1500	2013 RAM 1500	2013 FORD F-150	2013 TOYOTA TUNDRA
<b>ENGINE</b>					
Engine type	DOHC V8	OHV V6 (4.3) OHV V8 (4.8) OHV V8 (5.3) OHV V8 (6.2)	DOHC V6 SOHC V8 OHV V8	DOHC V6 (3.7) DOHC V6 turbo (3.5) DOHC V8 (5.0) SOHC V8 (6.2)	DOHC V6 (4.0) DOHC V8 (4.6) DOHC V8 (5.7)
Engine displacement (liters)	5.6	4.3 (V6) 4.8 (V8) 5.3 (V8) 6.2 (V8)	3.6 (V6) 4.7 (V8) 5.7 (V8)	3.7 (V6) 3.5 (V6 turbo) 5.0 (V8) 6.2 (V8)	4.0 (V6) 4.6 (V8) 5.7 (V8)
Horsepower (hp @ rpm)	317 @ 5200	195 @ 4600 (4.3) 302 @ 5600 (4.8) 315 @ 5200 (5.3) 403 @ 5700 (6.2)	305 @ 6400 (3.6) 310 @ 5650 (4.7) 395 @ 5600 (5.7)	302 @ 6500 (3.7) 365 @ 5000 (3.5) 360 @ 5500 (5.0) 411 @ 5500 (6.2)	270 @ 5600 (4.0) 310 @ 5600 (4.6) 381 @ 5600 (5.7)
Torque (lb-ft @ rpm)	385 @ 3400	260 @ 2800 (4.3) 305 @ 4600 (4.8) 335 @ 4400 (5.3) 417 @ 4300 (6.2)	269 @ 4175 (3.6) 330 @ 3950 (4.7) 407 @ 3950 (5.7)	278 @ 4000 (3.7) 420 @ 2500 (3.5) 380 @ 4250 (5.0) 434 @ 4500 (6.2)	278 @ 4400 (4.0) 327 @ 3400 (4.6) 401 @ 3600 (5.7)
Engine block	Aluminum alloy	Aluminum alloy (6.2) Cast iron (4.3, 4.8, 5.3)	Aluminum alloy (3.6) Cast iron (4.7, 5.7)	Aluminum alloy Cast iron (6.2)	Aluminum alloy
Timing-chain-driven camshafts	S	S	S	S	S
<b>DRIVETRAIN</b>					
Automatic transmission	5-speed	4-speed 6-speed	6-speed 8-speed	6-speed	5-speed 6-speed
Locking rear differential	A	A	N/A	A	N/A
<b>SUSPENSION AND STEERING</b>					
Front suspension	Independent	Independent	Independent	Independent	Independent
Rack-and-pinion steering (speed-sensitive)	S	S (not speed-sensitive)	S (not speed-sensitive)	S	S
<b>BRAKING</b>					
4-wheel disc brakes	S	A	S	S	S
Brake Assist	S	N/A	S	S	S
Electronic Brake force Distribution	S	S	S	S	S

For Dealer Personnel Only

Copyright 2013 by  
Nissan North America, Inc.



## 2013 TITAN VS PRIMARY COMPETITORS

	2013 NISSAN TITAN	2013 CHEVROLET SILVERADO 1500	2013 RAM 1500	2013 FORD F-150	2013 TOYOTA TUNDRA
<b>CHASSIS</b>					
Full-length box-section frame rails	S	S	S	S	Boxed front only
<b>WHEELS AND TIRES</b>					
Available wheels (in.)	18	17	17	17	17
	20	18	20	18	18
		20		20	20
		22		22	
<b>EXTERIOR</b>					
Utili-track® bed system	A	A (no floor channels)	A (no floor channels)	A (no floor channels)	A (deck rail system)
Lockable bedside storage compartment	A	N/A	A	A (midbox storage)	N/A
Spray-on bedliner	A	N/A	A	A	N/A
120-volt power outlet in cargo bed	A	N/A	N/A	A	A
Tailgate lock	S	A	S	S	S
Tailgate assist	A	A	N/A	S	S
<b>INTERIOR</b>					
Fold-flat front-passenger's seatback	A	N/A	N/A	N/A	A
<b>COMFORT AND CONVENIENCE</b>					
Rear air conditioning vents	A	A (under seat)	A (under seat)	S	A
Adjustable pedals	A	A	A	A	N/A
Auto-down/up for driver's and front-passenger's windows	S (all except S King Cab)	A (auto-down for driver only)	A	A (auto-down for driver only)	A
Keyfob-operated power-down front windows	A	N/A	A	N/A	N/A
Bluetooth® Hands-free Phone System <sup>1</sup>	A	S (OnStar)	A	A	A
RearView Monitor <sup>2</sup>	A	A	A	A	A
<b>SAFETY</b>					
Front-seat-mounted side-impact supplemental air bags <sup>3</sup>	S	S	S	S	S
Roof-mounted curtain side-impact supplemental air bags	S	S	S	S	S
Front-seat Active Head Restraints	S	N/A	N/A	N/A	N/A
<b>EXTERIOR DIMENSIONS</b>					
Wheelbase (in.)	139.8–159.5	119.0–157.5	120.5–140.5	125.9–163.1	126.8–164.6
Overall length (in.)	224.6–244.2	205.6–249.2	209.0–231.0	213.2–250.4	209.8–246.7
Overall width (in.)	79.5	79.9	79.4	79.2–86.3	79.9
Overall height (in.)	74.6–76.9	73.6–73.9	74.4–75.9	74.6–78.5	75.6–76.2
Minimum running ground clearance (in.)	10.2–11.4	8.9–9.3	8.6–9.3	7.9–9.5	10.0–10.6

## 2013 TITAN VS PRIMARY COMPETITORS

	2013 NISSAN TITAN	2013 CHEVROLET SILVERADO 1500	2013 RAM 1500	2013 FORD F-150	2013 TOYOTA TUNDRA
<b>EXTERIOR DIMENSIONS (cont.)</b>					
Cargo bed dimensions (in.):					
Length	79.1 (King Cab) 67.3–87.0 (Crew Cab)	69.3–97.8 (Extended Cab) 69.3 (Crew Cab)	76.3 (Quad Cab) 67.4 (Crew Cab)	67.0–97.4 (SuperCab) 67.0–78.8 (SuperCrew)	78.7–97.6 (Double Cab) 66.7 (CrewMax)
Maximum width	63.8	62.4	66.4	65.2	66.4
Width between wheel wells	50.0	50.6	51.0	50.0	50.0
Height	19.9	21.0	20.0–20.1	22.4	22.2
<b>INTERIOR DIMENSIONS</b>					
Head room front/rear (in.) (without moonroof):					
King Cab	41.0/38.9	41.2/39.2 (Extended Cab)	41.0/39.7 (Quad Cab)	41.0/39.7 (SuperCab)	40.2/38.7 (Double Cab)
Crew Cab	41.0/40.4	41.2/40.5 (Crew Cab)	41.0/39.9 (Crew Cab)	41.0/40.3 (SuperCrew)	40.2/38.7 (CrewMax)
Shoulder room front/rear (in.):					
King Cab	65.1/64.9	65.2/65.3 (Extended Cab)	66.0/65.7 (Quad Cab)	65.9/65.7 (SuperCab)	66.6/65.7 (Double Cab)
Crew Cab	65.1/64.6	65.2/65.1 (Crew Cab)	66.0/65.7 (Crew Cab)	65.9/65.5 (SuperCrew)	66.6/65.4 (CrewMax)
Hip room front/rear (in.):					
King Cab	61.3/60.3	62.5/61.9 (Extended Cab)	63.2/62.9 (Quad Cab)	60.5/65.4 (SuperCab)	63.0/62.6 (Double Cab)
Crew Cab	61.3/60.5	62.5/65.4 (Crew Cab)	63.2/63.2 (Crew Cab)	60.5/64.6 (SuperCrew)	63.0/62.6 (CrewMax)
Leg room front/rear (in.):					
King Cab	41.8/33.0	41.3/34.3 (Extended Cab)	41.0/34.7 (Quad Cab)	41.4/33.4 (SuperCab)	42.5/34.7 (Double Cab)
Crew Cab	41.8/40.4	41.3/38.7 (Crew Cab)	41.0/40.3 (Crew Cab)	41.4/43.5 (SuperCrew)	42.5/44.5 (CrewMax)
<b>CAPACITIES<sup>4</sup></b>					
Fuel tank capacity (gal.)	28.0	26.0–34.0	26.0–32.0	26.0–36.0	26.4
Towing capacity <sup>5</sup> (lbs.)	6500–9500	4700–10,700	3450–10,450	5500–11,300	4500–10,400

## 2013 TITAN VS PRIMARY COMPETITORS

	2013 NISSAN TITAN	2013 CHEVROLET SILVERADO 1500	2013 RAM 1500	2013 FORD F-150	2013 TOYOTA TUNDRA
<b>EPA MILEAGE ESTIMATES<sup>6</sup></b>					
Automatic transmission (city/hwy/combined) (mpg)	13/18/15 (4x2) 12/17/14 (4x4)	15/20/17 (4.3 4x2) 14/18/15 (4.3 4x4) 14/19/16 (4.8 4x2) 13/18/15 (4.8 4x4) 15/21/17 (5.3 4x2) 15/21/17 (5.3 4x4) 15/22/18 (XFE) 13/18/14 (6.2 4.2) 12/18/14 (6.2 4x4)	17/25/20 (3.6 4x2) 16/23/19 (3.6 4x4) 18/25/21 (3.6 HFE) 14/20/16 (4.7 4x2) 14/19/16 (4.7 4x4) 14/20/16 (5.7 4x2) 13/19/15 (5.7 4x4)	17/23/19 (3.7 4x2) 16/21/18 (3.7 4x4) 16/22/18 (3.5 4x2) 15/21/17 (3.5 4x4) 15/21/17 (5.0 4x2) 14/19/16 (5.0 4x4) 13/18/15 (6.2 4x2) 12/16/13 (6.2 4x4)	16/20/17 (4.0 4x2) 15/20/17 (4.6 4x2) 14/19/16 (4.6 4x4) 13/18/15 (5.7 4x2) 13/17/15 (5.7 4x4)
E85 (FFV only) (city/hwy/combined) (mpg)	9/13/11 (4x2) 9/12/10 (4x4)	10/14/12 (4.8 4x2) 10/13/11 (4.8 4x4) 11/16/13 (5.3 4x2) 11/16/13 (5.3 4x4) 11/16/13 (XFE) 9/13/11 (6.2 4x2) 9/13/10 (6.2 4x4)	12/17/14 (3.6 4x2) 11/16/13 (3.6 4x4) 10/12/11 (4.7 4x2) 10/12/11 (4.7 4x4)	12/17/14 (3.7 4x2) 11/15/13 (3.7 4x4) 11/15/13 (5.0 4x2) 10/14/12 (5.0 4x4)	9/12/11 (5.7 4x4) (non CA emissions)
<b>WARRANTY COVERAGE (LIMITED)</b>					
Basic (years/miles)	3/36,000	3/36,000	3/36,000	3/36,000	3/36,000
Powertrain (years/miles)	5/60,000	5/100,000	5/100,000	5/60,000	5/60,000
Corrosion (years/miles)	5/unlimited	6/100,000	5/100,000	5/unlimited	5/unlimited

<sup>1</sup> Availability of specific features is dependent upon the phone's Bluetooth® support. Please refer to your phone owner's manual for details. The Bluetooth word mark and logos are owned by Bluetooth SIG, Inc., and any use of such marks by Nissan is under license.

<sup>2</sup> Parking aid/convenience feature. Cannot completely eliminate blind spots or warn of moving objects. May not detect every object. Always check surroundings before moving vehicle. Not a substitute for proper backing procedures. Always turn to check what is behind you before backing up.

<sup>3</sup> Air bags are only a supplemental restraint system; always wear your seat belt. Even with the occupant-classification sensor, rear-facing child restraints should not be placed in the front-passenger's seat. Also, all children 12 and under should ride in the rear seat properly secured in child restraints, booster seats, or seat belts according to their size. Air bags will only inflate in certain accidents; see your owner's manual for more details.

<sup>4</sup> Cargo and load capacity limited by weight and distribution. Always secure all cargo.

<sup>5</sup> See Nissan Towing Guide and Owner's Manual for proper use.

<sup>6</sup> Actual mileage may vary with driving conditions — use for comparison only.